



WOYR2.E98031 Switches, Appliance and Special Use - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Switches, Appliance and Special Use - Component

[See General Information for Switches, Appliance and Special Use - Component](#)

GOTTAK S L


E98031

Pujades 77 6

08005 Barcelona, SPAIN

Investigated to ANSI/UL 61058-1

Cat. No.	Load	Amps	Volts	Hz	Temp (°C)	Pol/	Endurance		IP	Dis (mm)	SPCA	Std. Ed.
						Thr/ Cir	30C cycle	55C cycle				
Rotary												
7LA Series	RM	16(4)	250	50-60	T120	2/M-1.2, 1.3	6K	10K	40	full 3.0	-	2013-02-15
	RM	16(4)	250	50-60	T120	2/M-2.3, 4.3	6K	10K	40			
	RM	16(4)	250	50-60	T120	2/M-4.4, 4.5	6K	10K	40			
	RM	10(2)	400	50-60	T120	2/M-1.2,1.3	6K	10K	40			
	RM	10(2)	400	50-60	T120	2/M-2.3, 4.3	6K	10K	40			
	RM	10(2)	400	50-60	T120	2/M-4.4, 4.5	6K	10K	40			

Marking: Company name, catalog, model or part number, electrical ratings and the Recognized Component Mark,  on the product or on the smallest unit container in which the product is packaged.

Investigated to ANSI/UL 1054

Cat. No.	Amps	Volts	Hz	Load	Endurance	Temp C	POL/THR	Per Pole/ Circuit Code	SPCOA
210, 240, 250, 260 or 280 f/b 1,2,3 or 4, f/b w/wo suffixes									
	-	125	60	1/4hp	6K	65	1/1	PP/-	3
46 RCTH Series w/suffixes except B									
	12	250	60	GP	6K	115	1/M	-/-	3, Note 3, 4
	16	250	60	GP	6K				
	25	250	60	GP	6K				
	-	120	60	1hp	6K				
	-	240	60	2hp	6K				
46 RCTHB	12	250	60	GP	6K	70	1/M	-/-	3, Note 3, 4
	16	250	60	GP	6K				
	25	250	60	GP	6K				
	-	120	60	1hp	6K				
	-	240	60	2hp	6K				
4RH Series w/suffixes	12	250	60	GP	6K	105	2/M	-/-	Note 1, 2, 3
	16	250	60	GP	6K				
	-	120	60	1hp	6K				
	-	240	60	2hp	6K				

4RH w/suffixes	12	250	60	GP	6K	105	2/M	-/-	Note 5
	16	250	60	GP	6K				
	25	250	60	GP	6K				
	-	120	60	1hp	6K				
	-	240	60	2hp	6K				
7LA Series w/ suffixes	16	250	60	GP	6K	115	2/M	-/-	A1
	-	120	60	1hp	6K				
	-	240	60	2hp	6K				
	12	250	60	GP	6K				
	-	120	60	1hp	6K				
	-	240	60	2hp	6K				
7PA	12	250	60	GP	6K	105	2/M	-/-	Note 5
	16	250	60	GP	6K				
	25	250	60	GP	6K				
7PF Series w/suffixes	12	250	60	GP	6K	115	2/M	-/-	3, Note 3, 6, 7, 8
	16	250	60	GP	6K				
	25	250	60	GP	6K				
X-02 Series	10	250	60	GP	6K	65	2/1	PP/-	3

Note 1 - Current through common terminal shall not exceed 24A.

Note 2 - Current through "Dummy" terminal block shall not exceed 24A.

Note 3 - Each circuit may control up to the switch rating with same polarity between circuits.

Note 4 - Current through common terminal shall not exceed 32A.


Note 5 - Current through common terminal shall not exceed 30A.

Note 6 - Current through "Dummy" terminal block shall not exceed 25A.

Note 7 - Current through asterix marked "*" terminal shall not exceed 25A.

Note 8 - Current through common terminal shall not exceed 25A.

Note A1 - The switch is limited to a maximum of 30 A in any combination of circuit configurations.

Marking: Company name, catalog, model or part number, electrical ratings and the Recognized Component Mark,  on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2016-06-08

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".